

SMART ENERGY SOLUTIONS



LED Vertical Refrigerated Case Light

SES-T8V1532

PARAMETERS		
Model:		SES-T8V1532
Size:		5ft 1500mm
LED Specs:		SMD2835
LED Qty:		192 pcs
		V shape PCB
Power Consumption:		32W
CCT /CRI:		3000k/3500k/4000k/4500k/5000K/6500k CRI≥80
Luminance:	Clear cover	120lm/W
Net Weight:		420g
Certificates:		DLC
Material:		Aluminum+PC
Service Life:		50,000hrs
Warranty:		2 years Limited Warrnty
Beam Angle:		240°
Working Temperature:		-30℃~50℃
Electrical System		
Input Voltage:		AC100-277V
Input Current		MAX 0.4A
THD		<20%
Working Frequency:		50/60Hz
PFC:		≥0.95
Efficiency:		>88%
Package		
DLC		Inner white box+carton
LED Vertical Refrigerated Case Light		30pcs/carton

General Description

The model are T8 LED Vertical Refrigerated Case Light; the rating is 100~277Vac , 50/60 Hz

For dry and damp location.

- These lamps should be installed by an electrician;.
- Use in -30℃~50℃ environmental conditions;
- Do not install in a raceway or a luminary marked for through branch wiring.
- These devices are not intended for use with emergency exits.
- Always connect ground lead to fixture where applicable

SMART ENERGY SOLUTIONS



LED Vertical Refrigerated Case Light
SES-T8V1532



Be careful of electric shock

of electric shock.
ensure that power
source is off
when wiring or
soldering the

sections of the product.

Dimension

